



产品认证证书

证书编号：CQC19001219294

申请人名称及地址

喆光照明光电股份有限公司
新竹市龙山里7邻光复路一段472号6F之7

制造商名称及地址

喆光照明光电股份有限公司
新竹市龙山里7邻光复路一段472号6F之7

生产企业名称及地址

福建天电光电有限公司(V030775)
福建省泉州市安溪县湖头镇光电产业园

产品名称和系列、规格、型号

光电耦合器

见附件（仅适用于海拔5000米及以下）

产品标准和技术要求

GB4943.1-2011;GB8898-2011

认证模式

产品型式试验+获证后监督

上述产品符合CQC11-471543-2015认证规则的要求，特发此证。

发证日期：2019年05月21日

本证书的有效性依据发证机构的定期监督获得保持。

主任：_____

陆梅



中国质量认证中心

中国·北京·南四环西路188号9区100070

<http://www.cqc.com.cn>

C 0145876



PRODUCT CERTIFICATE

CERTIFICATE NO.: CQC19001219294

NAME AND ADDRESS OF THE APPLICANT

WISELITE Optronics Co., LTD.
6F-7, No. 472, Sec 1, Guangfu Rd., Hsinchu City 300, Taiwan

NAME AND ADDRESS OF THE MANUFACTURER

WISELITE Optronics Co., LTD.
6F-7, No. 472, Sec 1, Guangfu Rd., Hsinchu City 300, Taiwan

NAME AND ADDRESS OF THE FACTORY

FUJIAN LIGHTNING OPTOELECTRONIC CO.,LTD (V030775)
Photoelectric Industrial Park, Hutou Town, Anxi Country, Quanzhou City, Fujian Province, China

PRODUCT NAME, MODEL AND SPECIFICATION

Optocoupler
See appendix(Altitude up to 5000m)

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB4943.1-2011;GB8898-2011

TYPE OF CERTIFICATION SCHEMES

Type Testing of Product + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-471543-2015 .

Valid from: May.21,2019

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body.

President: _____

Lu Mei



CHINA QUALITY CERTIFICATION CENTRE

Section 9, No.188, Nansihuan Xilu, Beijing 100070 P.R.China
<http://www.cqc.com.cn>

C 0145876



产品认证证书

附 录

第 1 页 共 2 页

证书编号: CQC19001219294

纸 号: 145876

型号	内部爬电距离规格 (mm)	外部爬电距离规格 (mm)	内部穿透距离 (绝缘厚度) 规格 (mm)
MPC618XN (Y) (Z)-FGV, MPC810XN (Y) (Z)-GV, MPC814XN (Y) (Z)-GV, MPC8145XN (Y) (Z)-GV, MPC815XN (Y) (Z)-GV, MPC816XN (Y) (Z)-FGV, MPC816LXN (Y) (Z)-FGV, MPC817XN (Y) (Z)-FGV, MPC818XN (Y) (Z)-GV, MPC819XN (Y) (Z)-GV, MPC851XN (Y) (Z)-GV, MPC852XN (Y) (Z)-GV, MPC3010-4L (Y) (Z)-GV, MPC3011-4L (Y) (Z)-GV, MPC3012-4L (Y) (Z)-GV, MPC3021-4L (Y) (Z)-GV, MPC3022-4L (Y) (Z)-GV, MPC3023-4L (Y) (Z)-GV, MPC3051-4L (Y) (Z)-GV, MPC3052-4L (Y) (Z)-GV, MPC3053-4L (Y) (Z)-GV, MPC3071-4L (Y) (Z)-GV, MPC3072-4L (Y) (Z)-GV, MPC3073-4L (Y) (Z)-GV, MPC3031-4L (Y) (Z)-GV, MPC3032-4L (Y) (Z)-GV, MPC3033-4L (Y) (Z)-GV, MPC3041-4L (Y) (Z)-GV, MPC3042-4L (Y) (Z)-GV, MPC3043-4L (Y) (Z)-GV, MPC3061-4L (Y) (Z)-GV, MPC3062-4L (Y) (Z)-GV, MPC3063-4L (Y) (Z)-GV, MPC3081-4L (Y) (Z)-GV, MPC3082-4L (Y) (Z)-GV, MPC3083-4L (Y) (Z)-GV, MPCR21NX-4L (Y) (Z)-GV, MPCR41NX-4L (Y) (Z)-GV (在产品外包装的标签上体现完整型号, 上面所示型号中的变量解释如下: 其中X, N代表挡次, X可以是A-Z或空白, N可以是1-9或空白, Y代表脚型, 可以是M, S, SL, SLM, 空白 (表示DIP); Z代表编带类型, 可以是T1, T2, T3或T4;	N/A	≥ 7.6	≥ 0.4

注: 此附录与证书同时使用时有效。

主任: 陆梅



中国质量认证中心

中国·北京·南四环西路188号9区100070

<http://www.cqc.com.cn>

